



PANOLIN  
Bläsimühle 2 – 6  
CH-8322 Madetswil  
Telefon +41 44 956 65 65  
Telefax +41 44 956 65 75  
www.panolin.com  
info@panolin.com



## PANOLIN BOOMGREASE 2

**White lubricating grease – fully synthetic**

PANOLIN BOOMGREASE 2:

- White lubricating grease containing inorganic thickeners and PTFE additive
- Nontoxic
- Provides excellent protection against oxidation and corrosion
- High load-bearing capacity
- Excellent resistance to water

### Changing over to PANOLIN BOOMGREASE 2

For optimal performance, thoroughly clean the bearings and housing free of all old grease residues before regreasing. Do not mix with other greases.

### Applications (follow manufacturer's instructions)

- For lubricating joints, links and stuffing boxes, roller and sleeve bearings
- Ideal for crane jibs and booms

### Lube-Shuttle®

- Also available as PANOLIN SHUTTLE BOOMGREASE 2 (92222)  
– suitable for Lube-Shuttle® grease press

### Technical data (mean values, subject to normal tolerances)

Product No.	92221
NLGI	2
Soap/thickener type	Anorganic
Operation temperature range (permanent)	Up to 200 °C
Base	Synthetic
Colour	White

### Safety-relevant notes:

Please refer to the drum label, or for detailed information, to the safety data sheet (available from PANOLIN)